Compactors





Features

Plate compactor simple structures ensures long durability, easy handling and versatility of the machine.

Low centre of gravity provides greater stability and resilience against high vibration force.

Powerful compaction achieved with eccentric rotor and fully balanced plate.

Can be used for embankment, backfilling, roadbed compaction and asphalt surfacing work.

Motor or engine driven models available.

Specifications

Technical Data

Model	TKP-60	C-90	TKP-110	C-120
Base Plate Diameter (mm)	520 x 360	550 x 505	660 x 525	520 x 450
Exciter Speed (rpm)	5000	5000	6100	6100
Travel Speed (M/min)	Up to 28	Up to 25	Up to s36	Up to s36
Grade Ability (Deg)	Up to 25	Up to 23	25	Up to 25
Centrifugal Force (kn)	12	16.5	22	22
Min. Compaction Depth (cm)	20	25	30	30
Engine	Robin EY20D	Robin EY20D	Robin EY28D	Robin
Engine Type	Air-cooled Petrol	Air-cooled Petrol	Air-cooled Petrol	Petrol or Diesel
Max. Output (HP/rpm)	5,4000	5,4000	8,3600 / 9,3600	8,3600 / 9,3600
Starting System	Recoil	Recoil	Recoil	Recoil
Machine Weight (Kg)	60	90	110	120

September 07

Maxiito is the trading name of El Mechana Technical Equipment LLC for construction equipment

El Mechana Technical Equipment LLC

PO Box 181216

Dubai, United Arab Emirates

For a job well done, we are the one

Tel: +971 4 320 5599 Fax: +971 4 320 5499

Email: maxiitosales1@maxiito.ae